



Good bonds last.

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: Sabre CC Citrus Cleaner 3.5
Product Use: Adhesive Cleaner
Restriction of Use: Refer to Section 15

New Zealand Supplier: Sabre Adhesives Ltd
Address: 42 Cambridge Street South
Levin, 5510, New Zealand
Telephone: +64 (0)6 366 0007
Emergency No: **0800 764 766 (National Poison Centre)**

Australian Supplier: Sabre Adhesives Ltd
Address: Level 6, 10 Herb Elliot Avenue, Sydney NSW, 2127
Telephone No: +61 2 9098 8244
Emergency No: **13 11 26 (National Poison Line)**

Date SDS Issued: 3 May 2023 v4

Section 2. Hazards Identification

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

NZ - EPA Approval Code: Surface Coatings and Colourants (Subsidiary) - HSR002670

Pictograms



SIGNAL WORD: DANGER

GHS Category	Hazard Code	Hazard Statement
Flammable gas Cat. 1A	H220	Extremely flammable gas.
Liquefied Gas	H280	Contains gas under pressure may explode if heated.
	AUH044	Risk of explosion if heated under confinement.
Eye irritation Cat. 2	H319	Causes serious eye irritation.
	AUH066	Repeated exposure may cause skin dryness and cracking.

Product Name: Sabre CC Citrus Cleaner 3.5
Date of SDS: 3 May 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: +64 9 475 5240 WWW.techcomp.co.nz

specific target organ toxicity - single exposure Cat 3 - Narcotic Effects	H336	May cause drowsiness or dizziness.
---	------	------------------------------------

Prevention Code Prevention Statement

P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing fumes, gas, mist, vapours or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective clothing as detailed in Section 8.

Response Code Response Statement

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	In case of leakage, eliminate all ignition sources.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.

Storage Code Storage Statement

P403	Store in a well-ventilated place.
P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

Disposal Code Disposal Statement

P501	Dispose of according to the local authorities
------	---

Section 3. Composition of hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Acetone	60-80	67-64-1
LPG	20-40	68476-85-7

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
If on Skin	Take off contaminated clothing and wash before re-use. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/ attention.
If Swallowed	Rinse mouth thoroughly with water. Give plenty of water to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor/physician if you feel unwell.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:	Refer to Section 11 for further information.
Inhalation	May cause drowsiness or dizziness.
Ingestion	Not applicable.
Skin contact	Not applicable.
Eye contact	Causes eye irritation.

Section 5. Fire Fighting Measures

Hazard Type	Flammable Aerosolised liquid (canister).
Hazards from products	Carbon dioxide (CO ₂) other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. BEWARE: Empty solvent, paint, lacquer and flammable liquid drums present a severe explosion hazard if cut by flame torch or welded. Even when thoroughly cleaned or reconditioned the drum seams may retain sufficient solvent to generate an explosive atmosphere in the drum
Suitable Extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Precautions for firefighters and special protective clothing	Wear full body protective clothing with breathing apparatus. May be violently or explosively reactive. Prevent, by any means available, spillage from entering drains or water course. Consider evacuation. Fight fire from a safe distance, with adequate cover. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
HAZCHEM CODE	2YE

Section 6. Accidental Release Measures

Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.

Prevent, by any means available, spillage from entering drains or water course.

Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Approach the spillage from upwind. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush away spillage with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Section 7. Handling and Storage

Handling:

- Read carefully and follow all instructions.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Avoid breathing fumes, gas, mist, vapours or spray.
- Wash hands thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Wear protective clothing as detailed in Section 8.
- Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately. Check for bulging containers. Vent periodically. Always release caps or seals slowly to ensure slow dissipation of vapours.

Storage:

- Store away from incompatible materials listed in Section 10.
- Keep out of reach of children.
- Store locked up.
- Keep container tightly closed.
- Store in a well ventilated area.
- Check that containers are clearly labelled and free from leaks.
- Keep container tightly closed and protect from sunlight.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
LPG (Liquefied petroleum gas)	[68476-85-7]	1000	1800	-	-
Acetone	[67-64-1]	500	1185	1000	2375

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

Engineering Controls

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Personal Protection Equipment:



Eyes	Wear chemical goggles with side shields. Avoid wear contact lenses.
Hands	Insulated gloves: NOTE: Insulated gloves should be loose fitting so that they may be removed quickly if liquid is spilled upon them. Insulated gloves are not made to permit hands to be placed in the liquid; they provide only short-term protection from accidental contact with the liquid.
Skin	Wear non-sparking protective boots and static-free clothing.
Respiratory	Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent) Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory

	<p>protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.</p> <table border="1"> <thead> <tr> <th>Required Minimum Protection Factor</th> <th>Half-Face Respirator</th> <th>Full-Face Respirator</th> <th>Powered Air Respirator</th> </tr> </thead> <tbody> <tr> <td>up to 5 x ES</td> <td>AX-AUS / Class 1</td> <td>-</td> <td>AX-PAPR-AUS / Class 1</td> </tr> <tr> <td>up to 25 x ES</td> <td>Air-line*</td> <td>AX-2</td> <td>AX-PAPR-2</td> </tr> <tr> <td>up to 50 x ES</td> <td>-</td> <td>AX-3</td> <td>-</td> </tr> <tr> <td>50+ x ES</td> <td>-</td> <td>Air-line**</td> <td>-</td> </tr> </tbody> </table>	Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator	up to 5 x ES	AX-AUS / Class 1	-	AX-PAPR-AUS / Class 1	up to 25 x ES	Air-line*	AX-2	AX-PAPR-2	up to 50 x ES	-	AX-3	-	50+ x ES	-	Air-line**	-
Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator																		
up to 5 x ES	AX-AUS / Class 1	-	AX-PAPR-AUS / Class 1																		
up to 25 x ES	Air-line*	AX-2	AX-PAPR-2																		
up to 50 x ES	-	AX-3	-																		
50+ x ES	-	Air-line**	-																		
Other	Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.																				

Section 9 Physical and Chemical Properties

Appearance	Liquefied Gas (canister)
Odour	Not available
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	40°C
Melting Point / Freezing Point	-97°C
Freezing Point	Not applicable
Flash Point	-104°C
Flammability	Highly Flammable
Upper and Lower Explosive Limits	Not available
Vapour Pressure	46.86 kPa
Vapour Density (air=1)	2.93
Relative Density (water=1)	0.846
Solubility in water	Immiscible
Partition Coefficient:	Not applicable
Auto-ignition Temperature	Not available
Volatile organic Component	Not available
VOC	417.50 g/L
Particle Characteristics	Not applicable
Evaporation Rate	Not available

Section 10. Stability and Reactivity

Stability of Substance	Stable at normal ambient temperatures and when used as recommended. Stable at normal ambient temperatures and when used as recommended.
Conditions to Avoid	Avoid heat, sparks, flames and any other sources of ignition.
Incompatible Materials	Oxidising and combustible materials.
Hazardous Decomposition Products	Thermal decomposition or combustion products may include the following substances: carbon dioxide (CO2) other pyrolysis products typical of burning organic material.

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
Eye	The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.
Skin	Not applicable.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Individual component information:

Acute Toxicity:

Chemical Name	Oral – LD50	Dermal – LD50	Inhalation – LC50
Acetone	5800 mg/kg (rat)	>20000mg/kg (rat)	44 mg/L/4h (mouse)
LPG (liquefied petroleum gas)	-	-	658 mg/L/4hr (rat)
Naphtha petroleum, light, hydrotreated	>2000 mg/kg(rat)	>1900 mg/kg (rabbit)	>4.42 mg/L/4h (rat)

Sabre S105/Citrus Cleaner Canister Spray Adhesive:

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

ACETONE

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Section 12. Ecotoxicological Information

Not hazardous to the environment.

Acetone:

Endpoint	Species	Duration	Value LC50/EC50
NOEC(ECx)	Fish	12 hr	0.001 mg/L
EC50	Crustacean	48 hr	6098.4 mg/L
LC50	Fish	96 hr	3744.6-5000 mg/L
EC50	Algae or other aquatic plants	96 hr	9.873-27.684 mg/l

LPG (liquefied petroleum gas):

Endpoint	Species	Duration	Value LC50/EC50
EC50(ECx)	Algae or other aquatic plants	96 hr	7.71 mg/L
LC50	Fish	96 hr	24.11 mg/L
EC50	Algae or other aquatic plants	96 hr	7.71 mg/L

Persistence and degradability	No data available on product Acetone: Persistence: Water/Soil LOW (Half-life=14 days) Air MEDIUM (Half-life= 116.25 days)
Bioaccumulative	No data available on product Acetone: LOW (BCF=0.69)
Mobility in soil	No data available on product Acetone: HIGH (KOC = 1.981)
Other adverse effects	No data available

Section 13. Disposal Considerations

Disposal Method: Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Precautions and methods to avoid: Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

Section 14 Transport Information

**This product is classified as a Dangerous Good for transport in Australia; ADG 7
This product is classified as a Dangerous Good for transport: NZS 5433:2020 and SNZ HB 5433:2021**



Road, Rail, Sea and Air Transport

UN No	3501
Class - Primary	2.1
Proper Shipping Name	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S (contains LPG (liquefied petroleum gas)).
Marine Pollutant	NO
Special Provisions	274, 362 Limited Quantities: 0

Section 15 Regulatory Information

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Poison Schedule No: Not Scheduled

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Surface Coatings and Colourants (Subsidiary) - HSR002670

Controls in New Zealand:

Trigger quantities for this substance:

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	100kg
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250kg
Emergency Response Plan	300kg
Secondary Containment	300kg
Fire Extinguishers	50kg = 1
Restriction of Use	Only use for the intended purpose.

Section 16 Other Information

Glossary

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible

Product Name: Sabre CC Citrus Cleaner 3.5
Date of SDS: 3 May 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: +64 9 475 5240 WWW.techcomp.co.nz

UEL authority.
WES Upper Explosive Level
Workplace Exposure Limit

References:

Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. Standard for the Uniform Scheduling of Medicines and Poisons.
3. Australian Code for the Transport of Dangerous Goods by Road & Rail.
4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
5. Workplace exposure standards for airborne contaminants, Safe work Australia.
6. American Conference of Industrial Hygienists (ACGIH).
7. Globally Harmonised System of classification and labelling of chemicals.

New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 3 May 2023 Review Date: 3 May 2028